

HR642563

Electrical Specification @25°C

RoHS Compliant (PB Free)

Operating Temperature Range: 0°C ~ +70°C

Isolation: 1500Vrms 0.5mA 60sec (Primary to Secondary)

OCL: 100uH Minimum @100kHz 100mV

Insertion Loss: -2.0dB Maximum @300KHz ~ 1MHz / -1.8dB Maximum @1MHz ~ 600MHz
-2.2dB Maximum @600MHz ~ 800MHz

Return Loss : -20dB Minimum 1MHz ~ 40MHz / -14dB Minimum 40MHz ~ 250MHz
-11dB Minimum 250MHz ~ 600MHz / -9dB Minimum 600MHz ~ 800MHz

DCMR: -32dB Minimum 1MHz ~ 100MHz / -22dB Minimum 100MHz ~ 400MHz
-20dB Minimum 400MHz ~ 800MHz


CMRR: -32dB Minimum 1MHz ~ 100MHz / -22dB Minimum 100MHz ~ 400MHz
-20dB Minimum 400MHz ~ 800MHz

Crosstalk: -40dB Minimum 1MHz ~ 100MHz / -26dB Minimum 100MHz ~ 400MHz
-20dB Minimum 400MHz ~ 800MHz


Designed To Support 57VDC, 350mA per centre tap

(17.5W when using 2 centre taps; 35W when using 4 centre taps)

Schematics



Mechanical Dimensions



Dimensions in mm

Unless otherwise specified, Tolerance: .xx ±0.25

REV.: A0

1 of 1