

HR041188

Electrical Specification @25°C

RoHS Compliant (Pb Free)

Isolation: 1500VDC 0.5mA 60S (Pri. & Aux. to Sec.)

Isolation: 500VDC 0.5mA 60S (Windings to Windings, Windings to Core)

Pin2-1 Inductance: 6.8 μ H $\pm$ 10% @100KHz 1Vrms

Pin2-1 Leakage Inductance: 1.5 μ H Max. @100KHz 1Vrms (Shorted Other Windings)


Pin2-1 DC Resistance: 42 mohms TYP.

Pin4-3 DC Resistance: 376 mohms TYP.


Pin7-5 DC Resistance: 181 mohms TYP.

Turns Ratio: P2-1 : P4-3 : P7-5 = 9 : 9 : 17 @100KHz, 0.1Vrms

Schematics



Mechanical Dimensions



Unless otherwise specified,
 Tol.: .xx $\pm$ 0.25 (mm)


HR041188

MATERIAL LIST



NO.	ITEM	MATERIAL GENERIC NAME	TRADE NAME	MANUFACTURES OF MATERIAL	TEMP CLASS	UL NO.
1.	CORE	FERRITE CORE	PS40	SHENZHEN MAXMAGTHCH Co. , LTD		
		or EQUIVALENT				
2.	BOBBIN	PHENOLIC	PM9630	SUMITOMO BAKELITE Co.,LTD	94V-0	E41429
		or EQUIVALENT				
3.	WIRE	POLYURETHANE	1UEW	ZHUHAI SUNTEK WIRE Co. LTD.	180℃	E234867
				ELEKTRISOLA HANGZHOU Co . LTD .	180℃	E258243
		or EQUIVALENT				
4.	TAPE	POLYIMIDE FILM TAPE	PIA220	3M Taiwan Ltd	220℃	E305006
		POLYIMIDE FILM TAPE	1218	3M COMPANY	180℃	E17385
		or EQUIVALENT				
5.	EPOXY	EPOXY	G500	GUDAK CHEMISTRY TECH (DONGGUAN) LTD	94V-0	
		or EQUIVALENT				
6.	VARNISH	VARNISH	BC-346A	JOHN C DOLPH CO	180℃	E317427
7.	SOLDER	STANNUM BAR	Sn96.5Ag3Cu0.5	ANSON SOLDER &TIN PRODUCTS MADE LTD		
		or EQUIVALENT				

HR041188

Transformer Construction and Winding



NOTE:

-  BOBBIN
 VARNISH
 INSULATION TAPE 2.0mm

Figure

No.	COIL	TERMINAL	WIRE	TURNS	TAPE	Direction
1	N1	2 -- 1	ø0.18mm*3P 1UEW-H	9T	1T	针脚朝内
2	N2	7 -- 5	ø0.16mm*2P 1UEW-H	17T	1T	针脚朝内
3	N3	4 -- 3	ø0.13mm*1P 1UEW-H	9T	1T	针脚朝内