


HR911449BE

Electrical Specification @25°C

Isolation:	2250VDC Min.	0.5mA 60sec UTP Side to Chip Side
OCL:	350uH Min.	@100KHz 100mV with 8mADC
Insertion Loss:	-1.0dB Max.	@1MHz ~ 100MHz
Return Loss:	-18dB Min.	@1MHz ~ 30MHz
Return Loss:	-13.5dB Min.	@30MHz ~ 60MHz
Return Loss:	-12dB Min.	@60MHz ~ 80MHz
Cw/w:	35pF Max.	@100kHz 100mV
P1-3, P4-6 Q:	18 Min.	@100kHz 100mV
Designed to meet GR1089 Intra-Building Lightning Standard		

Schematics




HR911449BE

- RoHS Compliant (PB Free)
- Meets or Exceeds IEEE802.3 standards including 350uH Min OCL with 8mADC
- High performance for EMI suppression, Crosstalk, Return Loss and Consistent Electrical
- Minimum 2250VDC isolation per IEEE802.3 requirement
- Minimize PCB space and Simplify PCB Layout
- Less magnetic components to be placed on PCB, higher reliability and yields
- UL Recognized Component: File # E330599


Mechanical Dimensions




(Top View)



(Side View)



(Bottom View)



(Front View)

Standard LED	Wavelength	Forward V (Min/Max)	Forward A	Type
Green	568nm	1.8V/2.8V	20mA	squareness
Yellow	585nm	1.8V/2.8V	20mA	squareness

Dimensions in mm

Unless otherwise specified, Tolerance: .xx ±0.25

REV.: A2

2 of 4

DRAWN:

CHECK:


APPROVAL:

Tel: (0760)86103511 86103508 Fax: (0760)86103686 Post code: 528416

E-Mail: sales@hanrun.com <http://www.hanrun.com>

HR911449BE


PCB Layout



Recommended PCB layout (Component Side View)

All dimension tolerance are ± 0.08 unless otherwise specified

Suggested Panel Cutout



Dimensions in mm

Unless otherwise specified, Tolerance: .xx ± 0.25

REV.: A2

3 of 4

DRAWN:

CHECK:

APPROVAL:

Tel: (0760)86103511 86103508 Fax: (0760)86103686 Post code: 528416

E-Mail: sales@hanrun.com <http://www.hanrun.com>

HR911449BE

Material Specification

Housing: PA66 GF Black UL94V-0
Shield: 30u" Nickel over 0.20mm Thickness Brass
Insert: PA66 GF Black UL94V-0
Phosphor Bronze 0.35mm Thickness
Plating Area, 30u" gold over 50u" nickel
Solder Area, 100u" tin over 50u" nickel

Mechanical Performance:

Mating force: 5 lbs Maximum
Unmating force: 5 lbs Maximum
Plug to Jack Retention force: 20 lbs Minimum
Operating life: 750 Cycles Minimum

Operating and Storage Temperature:

Operating Temperature Range: -40°C ~ +85°C
Storage Temperature Range: -40°C ~ +85°C