

HR644831E

Electrical Specification @25°C

RoHS Compliant (PB Free)

Operating Temperature Range: -40°C ~ +85°C

Isolation: 1500Vrms 0.5mA 60sec (Primary to Secondary)

OCL: 120uH Minimum @100kHz 100mV 8mADC

Insertion Loss: -3.0dB Maximum @100kHz ~ 1MHz / -1.25dB Maximum @1MHz ~ 250MHz
-3.0dB Maximum @250MHz ~ 500MHz

Return Loss (load D+ to D-): -20dB Minimum 1MHz ~ 40MHz

-16dB Minimum 40MHz ~ 100MHz / -12dB Minimum 100MHz ~ 250MHz

-8dB Minimum 250MHz ~ 500MHz

DCMR: -35dB Minimum 1MHz ~ 100MHz / -30dB Minimum 100MHz ~ 250MHz


-25dB Minimum 250MHz ~ 500MHz

CMRR: -35dB Minimum 1MHz ~ 100MHz / -27dB Minimum 100MHz ~ 250MHz



-25dB Minimum 250MHz ~ 500MHz

Crosstalk: -35dB Minimum 1MHz ~ 100MHz / -25dB Minimum 100MHz ~ 500MHz

Schematics



Mechanical Dimensions



Dimensions in mm

Unless otherwise specified, Tolerance: .xx ±0.25

REV.: 00

1 of 1